

COVERAD

Coverwall Hygienic Wall Cladding

Datasheet

Specification Summary



A clean, durable wall cladding system for healthcare, education, washrooms, corridors and other hard-working interiors.

Overview

Coverwall is a hygienic PVC wall cladding solution supplied by Coverad for projects that need a smart, wipe-clean and durable finish.

It is designed for use in interiors where appearance, hygiene and long-term practicality matter — including healthcare support spaces, education settings, washrooms, changing areas, kitchens, utility rooms and commercial back-of-house areas.

Installed with adhesive and finished with trims or sealant, Coverwall helps create a smooth finished surface with a professional appearance.



Coverwall sheet material

Key features

<p>Impact resistant</p> <p>Suitable for demanding interiors and day-to-day wear.</p>	<p>Fire-rated material</p> <p>Class B-s2, d0 to EN 13501 and UL 94 V0 stated in source data.</p>	<p>Waterproof / moisture resistant</p> <p>A practical fit for washrooms, wet areas and service spaces.</p>
<p>Chemical resistant</p> <p>Designed for environments that require practical, easy-care surfaces.</p>	<p>Easy-care finish</p> <p>Supports regular cleaning and helps walls stay looking smart.</p>	<p>Trimmed installation system</p> <p>Installed with adhesives plus jointing / corner trims or sealant.</p>

Specification

Coverwall Hygienic Wall Cladding — quick technical summary

Category	Detail
Material	Rigid hygienic PVC wall cladding sheet.
Standard sheet sizes	2440 x 1220 mm and 3050 x 1220 mm.
Typical thicknesses	2.3 mm or 2.5 mm depending on selected finish / colour.
Finishes	Gloss and satin options available depending on colour.
Installation	Installed with adhesive and finished with trims / profiles or sealant.
Profiles available	Jointing, angle and corner trims for neat internal corners, external corners and sheet junctions.
Operating temperature	-15°C to +60°C stated in source brochure.
Density	1.44 g/cm ³ stated in source data.
Fire performance	EN 13501: B-s2, d0. UL 94 V0 also stated in source data.
Water absorption	1.0% stated in source data.
Typical applications	Healthcare, education, washrooms, changing areas, kitchens, corridors, utility rooms and commercial back-of-house spaces.

Colour options

White gloss, white satin, buttermilk beige satin, arctic blue satin, mink grey satin, tin grey satin, pewter grey gloss, ocean blue gloss, peppermint green gloss and black gloss.

Ideal for Healthcare support areas, washrooms, education spaces, commercial interiors and back-of-house areas.	Why clients choose it A clean look, easy-care finish and practical long-term durability in demanding spaces.	Coverad support Quotation support, take-off help, trim advice and a coordinated package alongside pipe boxing or radiator covers.
--	--	---

For quotations and project support

Send wall sizes, sketches, drawings or photos and Coverad can help build a practical wall cladding package including sheets, trims and accessories.